

# Down South Vettes Leather console cover Installation Instructions.

**Difficulty:** 1 out of 5.

**Time:** Plan on about 5 minutes.

**The tools used are:**

- ? A T15 Torx driver to take off the console cover screws.
- ? A flashlight may help get a better look at the screw location as you start.

We are ready to install a Down South Vettes leather console cover.

**The OEM cover to replace:**



Open the cover to reveal the four T15 Torx screws that hold the cover in place:



**Remove the four Torx screws and then remove the console cover. Take caution as you remove the last screw. The console cover can fall off and you don't want to damage your cover or interior at this point. Remove the last screw with your left hand while holding the top center of the cover with your right hand.**

**Here are the two covers side by side:**



**And a close up to get a look at the added padding in the DSVettes cover:**



**You simply need to reverse the process now to install the new DSVettes cover in place of the old OEM cover.**

**Seated in the drivers seat, hold the cover in place with your right hand and with one of the screws in your left hand. Find the threaded hole and start the first screw. Once the threads start, take out your driver with the Torx T15 insert and tighten the screw most of the way. While still holding the cover, start one of the remaining four screws with your left hand. When both of these are in tight, you can release your grip on the console cover. Insert and tighten the remaining two screws and sit back and enjoy your new console cover.**

Once complete it will look like this:



<http://www.dsvettes.com/index.htm>